## BEARING:NDE, PART # 7312 BT1 DBC3

	BEARING,BALL, PART # 7305 BG	Pair	4
	BEARING, BALL, SINGLE ROW, DUPLEX ANGULAR CONTACT,		
	MATCHED PAIR, MEDIUM SERIES, WITH STEEL CAGE, METRIC SIZES.		
	(NON-METALLIC CAGE NOT ACCEPTABLE)		
	DIMENSIONS: ID 25 X OD 62 X WIDTH 34MM	_	
8	BEARING, BALL, PART # 6210-C3	Ea	1
	BEARING, BALL, RADIAL, SINGLE ROW, RIGID JOURNAL, CONRAD TYPE, LIGHT SERIES, WITH RADIAL CLEARANCE GREATER THAN NORMAL, METRIC SIZES, WITH STEEL CAGE.		
	(NON-METALLIC CAGE NOT ACCEPTABLE)		
	DIMENSIONS: ID 50 X OD 90 X WIDTH 20MM		
9	BEARING, BALL, PART # 6212	Ea	1
	BEARING, BALL, RADIAL, SINGLE ROW, RIGID JOURNAL,		
	CONRAD TYPE, LIGHT SERIES, METRIC SIZES,		
	WITH STEEL CAGE.		
	(NON-METALLIC CAGE NOT ACCEPTABLE)		
	DIMENSIONS: ID 60 X OD 110 X WIDTH 22MM		
10	BEARING, PART # NU309	Ea	1
	BEARING, ROLLER, CYLINDRICAL, RIGID RADIAL, SINGLE ROW,		
	SELF-CONTAINED OUTER RACE AND STRAIGHT INNER		
	RACE, WITH STEEL CAGE, MEDIUM SERIES. METRIC SIZES.		
	(NON-METALLIC CAGE NOT ACCEPTABLE)		
	DIMENSIONS: ID 45 X OD 100 X WIDTH 25MM		
11	BEARING:NDE, PART # 7312 BT1 DBC3	Ea	1

## SPARES FOR FUJI MOTOR

INDUCTION MOTOR, TYPE: MLA1310D, FRAME: 315 S,

100 HP, 440 VOLT, 117 AMP, 50 HZ, 3 PHASE, 2 POLES,

2965 RPM, RATING: M.C.R., INSULATION CLASS F,

COOLANT 50 DEG. C, RULE: 1EC34-1-1969,

TYPICAL SR.NO. 84118258DS-1,

NON-SPARKING MOTOR SUITABLE FOR CL 1-DIV.2 GR.D.

(FOR EBARA STRIPPED SOUR WATER PUMPS, MODEL: 100 LPWM (40H), SR.NO. RE10256-04,

BEARING, NON DRIVE END SIDE,

**DIMENSIONS: N/A** 

12 BEARING,BALL:DEEP GROOVE,

13

Ea 1

**ROW 1,20 MM ID,47 MM OD,14 MM WD,OPEN, PART # 6204** 

BEARING, BALL, RADIAL, SINGLE ROW, RIGID JOURNAL,

CONRAD TYPE, LIGHT SERIES, METRIC SIZES.

(METALLIC CAGE/ RETAINER'S ONLY)

DIMENSIONS: ID 120 X OD 20 X WIDTH 14MM BEARING,BALL PART # 3206

BEARING, BALL, ANGULAR CONTACT, DOUBLE ROW, LIGHT

SERIES, WITH STEEL CAGE, METRIC SIZES.

(NON-METALLIC CAGE NOT ACCEPTABLE)

**DIMENSIONS: ID 30 X OD 62 X WIDTH 23.81MM**